PRODUCT CATALOG

TMXFLOW

SB - 200
HORIZONTAL BLENDER



SB - 200
Horizontal Blender



Application

SB200 blender is used to dissolve solid / powder products in to a liquid, recirculated in a tank. The blender is limited to the suction of small amount of solids as it has no table for bags and the hopper is smaller than that of the table blender.

Working Principle

SB200 blender is a compact unit, it consists of a centrifugal pump witha venturi system on the suction side and a hopper with a butterfly valve above the venturi to add solid / powder products to the pumped liquid. The venturi system and the suction of the pump create a negative pressure at the base of the hopper. To achieve the best possible dissolution, it is recommended to recirculate the product.

Options

- Gaskets FPM or PTFE
- Connections DIN, SM
- Vibrator for hopper.
- Pneumatically actuated valve + low level sensor for solids.
- Solids upper level sensor

Design and Features

- Easy assembly and cleaning
- Hygienic design.
- Single Mechanical seal
- ISO 2852 Clamp connections for easy assembly /disassembly.
- Cleaning and disinfection without disassemby

Materials


Parts in contact with the product	AISI 316L
Other metal parts	AISI 304
Gaskets	EPDM
Mechanical seal	SiC/C/EPDM
Internal Bright Polish Ra	0,8 µm
External Mat	


SB - 200
Horizontal Blender

TMXFLOW
let it flow

DIMENSIONS							
TYPE	ØDN	A	B	C	D	E	F
SB-200	3″	950	438	1380	410	170	615

CAPACITY				
Liquid (m^3/h)	Powder (kg/h)	Power (kw)	Speed (rpm)	Weight (kg)
65	9	11	3000	240







www.quantumengineering.be
sales@quantumengineering.be
Quantum Engineering BV
Corsicalaan 9
B-2950 Kapellen
Tel. +32(0)467.00.77.72.